

POWERFUL AND FAST CUTTING



Technical data	THE RESERVE OF THE PARTY OF THE
Characteristics	
Grinding wheels (Ø x bore)	355 x 25.4 mm // 14 x 1 "
Torque .	18 Nm / 160 in-lbs
No-load speed	4000 rpm .
Rated input power	2300 W
Max. cutting capacity round tube	125 mm / 5 *
Max. cutting capacity rectangular tube	115 x 130 mm // 4 1/2 x 5 1/8 "
Olmensions of the base place	468 x 262 mm // 16 7/16 x 11 3/32
Transport height	400 mm / 15 3/4 "
Weight	16.9 kg / 37 lbs
Cable length	2.7 m / 9 ft
Naise emission	
Sound pressure level	91 dB(A)
Sound power level (Ew/k)	TOT OB(A)
Uncertainty of measurement K	3 dB(A)

Metal Chop Saw 14" - CS23-355 (602335380)

- Easy to transport due to built-in hande and locking device
- For single phase alternating current
- Powerful and fast cutting for profiles, pipes and rods made of steel, cast iron, aluminium and other non-ferrous metals
- Motor and gear with ball bearing for high loads
- Spindle lock for easy disc change
- Quick clamping device with variable mitre conversion from -15° up to 45°
- High safety thanks to swivelling cutting guard
- Storage for double-ended wrench at the machine table
- Safe working thanks to adjustable spark guide plate
- Adjustable cutting depth limiter