



- The , construction vehicles, and supporting products of construction machinery and agriculture machinery such as washing automobiles, bulldozers, concrete mixers, and tractors, etc. It is the most ideal cleaning tool for personal and small-sized vehicle maintenance organizations to clean autos and motorcycles. The cleaning on outer walls, terrace, common bathing pools, and swimming pools of buildings with special effect on doors and windows, grounds, toilets, greasy dirt, and corners which are difficult to clean. The disinfection and cleaning of food processing factories, food processing machinery, and kitchens in hotels and restaurants.

MODEL

HP-CC2175

Power Supply Voltage	240V - 50Hz
Rated Power Watt / HP	2200w / 3HP
Working Pressure	155 Bar / 2175 psi
Flow Rate (L/min)	13
Protection Degree	IPX5
Industrial Motor	100% Copper wire
Hose	10m
Max. Water Temperature	50°C
Weight	35kg
Dimensions	630 x 480 x 520 mm
Packing Ctn.	1 unit



MODEL

HP-CC2500

Power Supply Voltage	240V - 50Hz
Rated Power Watt / HP	3000w / 4HP
Working Pressure	175 Bar / 2500 psi
Flow Rate (L/min)	14
Protection Degree	IPX5
Industrial Motor	100% Copper wire
Hose	10m
Max. Water Temperature	50°C
Weight	50kg
Dimensions	700 x 490 x 550 mm
Packing Ctn.	1 unit